



Example: TC-K1-N-N-M6-2000-SS-GD  
 Thermocouple type K  
 Code: K1  
 Without probe  
 M6 screw  
 2 meters lead wire  
 stainless steel lead wire  
 Grounded type

### Ordering Information(quick ordering code TC-K1 or TC-J1 TC-T1)

**TC-K1**, Thermocouple type K, code K1

**TC-J1**, Thermocouple type J, code J1

**TC-T1**, Thermocouple type T, code T1

— 1 — 2 — 3 — 4 — 5 — 6

#### 1:Probe diameter

**N** Not applicable for this sensor

#### 2:Probe length

**N** Not applicable for this sensor

#### 3:Screw type

**M6** M6 screw  
**M8** M8 screw  
**1/4BSP** 4/1 BSP screw

#### 4:Lead wire length(unit:mm),lead wire length is customized, can be any length you want

**2000** 2000mm lead wire  
**3000** 3000mm lead wire  
**5000** 5000mm lead wire

#### 5:Lead wire material

**SS** Stainless steel wire  
**SILI** Silicon wire  
**FG** Fiber glass insulation wire  
**TF** Teflon wire

#### 6:Grounded or ungrounded type

**GD** Grounded type(standard one, also known as non-isolation type)  
**UG** Ungrounded type(also known as isolation type)