



Example:TC-K2-5-100-M8-2000-SS-GD
 ThermocoupletypeK
 Code:K2
 Probediameter:5mm
 Probelength:100mm
 M8screw
 2metersleadwire
 stainlesssteelleadwire
 Groundedtype

OrderingInformation(quickorderingcode TC-K2or TC-J2 TC-T2 TC-E2)

TC-K2, ThermocoupletypeK,codeK2
 TC-J2, ThermocoupletypeJ,codeJ2
 TC-T2, ThermocoupletypeT,codeT2
 TC-E2, ThermocoupletypeE,codeE2



1:Probediameter(mm),customizable,othersizenotlistedbelowbutalsoavailable

2	Probediameter2mm
3	Probediameter3mm
4	Probediameter4mm
5	Probediameter5mm

2:Probelength(mm),customizable,othersizenotlistedbelowbutalsoavailable

50	Probelength50mm
100	Probelength100mm
150	Probelength150mm
200	Probelength200mm

3:Screwprocessfittingstype (otherspecsavailable,pleasediscusswithoursalesperson)

M8	M8screw
1/2NPT	1/2NPT
M6	M6screw

4:Leadwirelength(unit:mm), leadwirelengththiscustomized,canbeanylengthyouwant

2000	2000mmleadwire
3000	3000mmleadwire
5000	5000mmleadwire

5:Leadwirematerial

SS	Stainlesssteelwire
SILI	Siliconwire
FG	Fiberglassinsulationwire
TF	Teflonwire

6:Groundedorungroundedtype

GD	Groundedtype(standardone,alsoknownasnon-isolationtype)
UG	Ungroundedtype(alsoknownasisolationtype)