



Example: TC-K2-5-100-M8-2000-SS-GD
 Thermocouple type K
 Code: K2
 Probe diameter: 5mm
 Probe length: 100mm
 M8 screw
 2 meters lead wire
 stainless steel lead wire
 Grounded type

Ordering Information(quick ordering code TC-K2 or TC-J2)

TC-K2, Thermocouple type K, code K2
 TC-J2, Thermocouple type J, code J2



1: Probe diameter(mm), customizable, other size not listed below but also available

2	Probe diameter 2mm
3	Probe diameter 3mm
4	Probe diameter 4mm
5	Probe diameter 5mm

2: Probe length(mm), customizable, other size not listed below but also available

50	Probe length 50mm
100	Probe length 100mm
150	Probe length 150mm
200	Probe length 200mm

3: Screw process fittings type(other specs available, please discuss with our sales person)

M8	M8 screw
1/2NPT	1/2 NPT
M6	M6 screw

4: Lead wire length(unit:mm), lead wire length is customized, can be any length you want

2000	2000mm lead wire
3000	3000mm lead wire
5000	5000mm lead wire

5: Lead wire material

SS	Stainless steel wire
SILI	Silicon wire
FG	Fiber glass insulation wire
TF	Teflon wire

6: Grounded or ungrounded type

GD	Grounded type(standard one, also known as non-isolation type)
UG	Ungrounded type(also known as isolation type)